



## TECHNICAL DATA SHEET

### Gate Valve Lockout



- Set of five gate valve lockouts Suitable for 25mm to 330mm gate valves.
- Completely surrounds the valve handle to prevent accidental operation.
- Center knockout can be removed for rising stem gate valves.
- With eye-catching safety warning labels, it supports language types, layout adjustments.
- Durable, lightweight temperature difference resistance -30 ~ 140°C thermoplastic material is chemical resistant and performs effectively in extreme environments.
- Valve locks are recommended to be used in conjunction with steel padlocks and safety signs to achieve energy isolation, equipment locking, and prevention of misuse.

Model	Inner Hole (mm)	Inner Diameter (mm)	Inner Height (mm)	Hand Wheel Diameter
BM-SGVL01	19	70	28	25-64 mm (1"-2.5")
BM-SGVL02	44	130	35	64-127 mm (2.5"-5")
BM-SGVL03	62	170	42	127-165 mm (5"-6.5")
BM-SGVL04	88	265	60	165-254 mm (6.5"-10")
BM-SGVL05	105	355	60	254-330 mm (10"-13")

#### Product Application

The Gate Valve Lockout Device Suitable for 1in (25mm) to 13in (330mm) diameter valve handles to surround the valve operating handle to protect against accidental valve opening. Tough, lightweight, dielectric Zenez™ Thermoplastic body withstands chemicals and performs effectively in extreme conditions. Includes high visibility permanent safety labels.

Country of Origin: China

Safeguard Your Business With Our Advanced Environmental Protection and Industrial Safety.  
Make A Call Right Now USA: +14695458710, [info@bullmansafety.com](mailto:info@bullmansafety.com)