



TECHNICAL DATA SHEET

Bullman Lifebuoy Ring SOLAS, with Retroreflective



The O-ring life buoy is made in high density polyethylene filled with polyurethane closed cell foam, SOLAS reflective tape and grab line. YIBEI has 2 life rings approved of SOLAS/MED/EC by DNV, 2.5 kg. These lifebuoys are tested and approved as per the most latest Regulations/Standards: Regulation (EU) 2020/1170, item No. MED/1.1. SOLAS 74 as amended, Regulation III/4, III/7, III/34 & X/3, LSA Code, 2000 .

Specifications

- Materials: high density polyethylene HDPE shell
- Buoyancy material: polyurethane PU foam
- Grab line: braid of high density polyethylene Ø 10 mm
- Color: Safety orange
- Thickness: 2 mm
- Maximum installation height, drop height: 80 meters

Features

- Tested under -62 °C.
- Sturdy out shell structure.
- Excellent anti UV treatment

Weight	Outside Diameter	Inside Diameter	Buoyancy	Approval
≥2.5 kg	720 mm	440 mm	≥142N	SOLAS/EC/MED

Item Code: BM-SOLAS-LR

Make: China

Safeguard Your Business With Our Advanced Environmental Protection and Industrial Safety.
Make A Call Right Now USA: +14695458710, info@bullmansafety.com